

J-TRAC HANGER, ROBUST



No ligature fixation possibility, a string around a hanger och hangers will release at an abnormal vertical load

- Self-harm and suicide resistant
- Durable hanger compatible with rail and suicide resistant hook
- Washable

Don't avoid clothes hangers for safety reasons We have developed a secure system for hangers and these hangers release from the rail or the suicide resistant hook when loaded above secure loads. For detailed information please see the Product data section below

PRODUCT DATA

Material

J-trac hanger, light - paper – Cross layered* cardboard and Polyurethane J-trac hanger, light – Polyurethane J-trac hanger, robust – Polyurethane Rail and end stops – Aluminum Disc - Thermoplastic polyurethane, TPU *Manufacturing method to make corrugated cardboard more durable and stable.

Sustainability

J-trac hanger, robust and disc have a very long durability. J-trac hanger, light, robust and disc are recycled as plastic. J-trac hanger, light - paper as cardboard. Rail and fittings as metal.

Warranty

5 years warranty: J-trac hanger system - Rail and end caps. 2 years warranty: J-trac hanger disc, J-trac hanger, robust and J-trac hanger, light. J-trac hanger, light – paper are disposable products and no warranty is applicable. Orders will be shipped within 2-3 weeks. For special orders, delivery times may vary. For questions, offers or order please contact: info@healsafeinterior.com

data

1 hanger releases at 3.9 kg load 5 hangers release at 13.6 kg load Hanger dimensions: width 420 mm, height 200 mm J-trac hanger system is adapted to wardrobes with a width of 600 mm or less, but can also be adapted for larger widths. Manufactured in Sweden. Tested at RISE, Sweden.

Maintenance

Rail and J-trac hanger robust and light can be cleaned with alcohol or detergents. J-trac hanger, light – paper can be cleaned with a dry cloth.

Delivery

Lead time from order is 2 weeks.

Mounting

Mount the rail with security screws JT-283. Snap disc open to replace or change hanger. Installation manual will be provided at order or on request.